




Element: 036

Models: 1E036, 2E036, 2F036, 4F036
4G036, 6G036, 6H036

Use appropriate HP and pressure scales for the number of stages required.

NOTE: Pressure limits rated at 87 psi/stage (70 Duro.) Some models have additional limits. Please consult factory before making final selection.

	RPM	150	300	450	600	650
NPSH Required — (Ft.)		1.50	3.10	5.60	9.50	10.80
Minimum Recommended Motor HP	1 STG	3	5	7½	10	10
	2 STG	5	7½	10	15	15
	4 STG	7½	15	20	25	25
	6 STG	10	20	25	30	40
Drive End HP Must be added to HP value from curve.	E	0.24	0.48	0.72	0.96	1.16
	F	0.38	0.76	1.10	1.50	1.70
	G	0.53	1.10	1.60	2.20	2.30
	H	0.90	1.70	2.60	3.50	3.80



*(PSI × .069 = BAR) (PSI × .070 = kaf/cm²) (USGPM × .2271 = M³/HR) (HP × .746 = kW)

Continental Pump Company

29425 State Hwy B | Warrenton, Missouri 63383 | Tel: 636-456-6006 | Fax: 636-456-4337 | Email: sales@con-pump.com
Visit us at: www.continentalultrapumps.com