


# Continental Progressive Cavity Pump CP Model CP15 Packed Seal Pump




### **Continental Pump Company**



### **CP Model Number Nomenclature:**

Materials used in the pumps are based on the fluid to be handled and are indicated in the model number nomenclature.



- (1): Indicates the pump model designation (CP, CPM, CPML Model)
- (2): Indicates the pump frame size designation
- (3): Indicates the pump body casting material
- (4): Indicates the rotor material
- (5): Indicates the stator material
- (6): Indicates seal type: Mechanical Seal or Packed Seal (For Mechanical use M, for Packed use D)
- (7): Indicates if the Drive Shaft, Flex Joint, and Rotor is Pinned or Threaded. (For pinned use P, for threaded use T)
- (8): Indicates if the pump has vertical suction housing. If horizontal is preferred no designation will be used.

#### Material of Construction

Continental Part Description	Continental Letter Designation	Part Materials
Pump Body	С	Cast Iron
	S	316 Stainless Steel (CF8M)
Rotor	D	Chrome Plated Alloy Steel
	S	Chrome Plated Stainless Steel
Stator	Q	Buna Nitrile
	В	EPDM
	F	Viton®
Seal Type	М	Mechanical Seal
	D	Packing Gland

Mechanical Seal and Packed Seal options are available for all frame sizes (15, 22, 33, 44, 56, and 67).

The Pinned Drive Shaft, Flex Joint, and Rotor option is also available for all frame sizes. The Threaded option is available only in frame sizes 15, 22, 33, 44, and 56; Size 67 has pinned option only.



# CP Pump

### Replacement Parts for CP15 Packed Seal Pump

Part	Part Name	Continental Pump Part Number	For Continental Pump Model
	Suction Body	CP1-15C CP1-15S	CP15
	Suction Body, Vertical	CPV1-15C CPV1-15S	CP15
	Discharge Housing for Packed Seal with 1/8" NPT Drain Plug (Plug Sold Seperately)	CP3-15DC CP3-15DS	CP15
	Flexible Joint, Pinned	U2-15PQS U2-15PBS U2-15PFS	CP15
	Flexible Joint, Threaded	U2-15TQS U2-15TBS U2-15TFS	CP15
CHILLIE OF THE PARTY OF THE PAR	Rotor, Pinned & Threaded	U4-15PTS	CP15
	Stator	U5-15Q U5-15B U5-15F	CP15
	Stator Barrier (Optional)	U5R-15S	CP15
	Shaft, Pinned	U6-15PDS	CP15



Part	Part Name	Continental Pump Part Number	For Continental Pump Model
	Shaft, Threaded	U6-15TDS	CP15
0	Ball Bearing (2 Required)	U7-15	CP15
$\bigcirc$	Retaining Ring	U9-15	CP15
	1/8" NPT Drain Plug for Discharge Housing (Sold individually or in Bolt Kit)	U12-15C U12-15S	CP15
8	1/8" NPT Non Vented Grease Fitting	U13-15C	CP15
9	Packing Set, Teflon Coated	U14-15FC	CP15
609	Packing Gland	U15-15DC U15-15DS	CP15
0	Packing Gland Insert	U16-15S	CP15
	Roll Pins (for Pinned Pump Only, 2 Required)	U17-15S	CP15
	Lantern Ring	U19-15S	CP15
0	Shaft Retaining Ring	U20-15	CP15
0	Stator Ring	U28-15S	CP15
	Bearing Spacer	U29-15	CP15



## **CP Pump**

### Replacement Kits for CP15 Packed Seal Pump

Part	Part Name	Continental Pump Part Number	For Continental Pump Model
CHANGE OF SERVICE OF	Pinned Rebuild  Kit: Includes: QTY 1: Flex Joint, Rotor, Stator, Packing Set; Qty 2: Poll Pins	CPD15K-PQS CPD15K-PBS CPD15K-PFS	CP15
0.0000000 Areasons 0	Threaded Rebuild Kit: Includes: QTY 1: Flex Joint, Rotor, Stator, Packing Set.	CPD15K-TQS CPD15K-TBS CPD15K-TFS	CP15
s stoe stoe	Bolt Kit: Includes Qty 8: Housing Bolts, Washers & Nuts. Qty 2: Packing Gland Bolts & Washers. Qty 1: 1/8" NPT Drain Plug & 1/8" NPT Non- Vented Grease Fitting	U10-15DC	CP15



#### **Materials of Construction**

All Continental Pump casting materials are Class 40# grey cast iron and CF8M (316) stainless steel. The best metal for your application would depend on how corrosive your liquid is. We offer an epoxy coating for an additional charge and can be applied to the suction housing and discharge. The epoxy seals the cast iron from the material being pumped.

Stators are available in 3 types of elastomers. The rubber materials are: Buna Nitrile, EPDM and Viton<sup>®</sup>. The rubber that is best for your application depends on what liquid you are pumping and at what temperature, as it plays a vital role in which to select.

The rotors are available in Chrome Plated Stainless Steel.

Abrasive Resistance Mechanical Seals are a great upgrade for your more abrasive applications. By adding a <u>Stator Barrier</u>, which is recommended in any negative suction and/or vacuum application to help protect the stator. There are lots of variables to take in consideration to know if this is right for your application. Contact us with your application information to see if this is for you.

**Looking for simplicity?** We offer complete Progressive Cavity Pump Units. They are constructed on a steel base to fit your specific application needs. The Unit consists of a Pump, a Steel Base & Guard, a Gear Reducer and Motor. Also available are Belt Drive Units, Gas or Diesel Engines, and many other base options.

**Space Challenged?** If you are needing a different arrangement from traditional piping, we have vertical suction housings available in the CP Model.

Don't need a complete pumping unit but looking for drive options? We can still help, whether attached to a pump or sold separately we can supply you with VFD's, Motors and Bases.